

<p>Tekstilna tovarna OKROGLICA d.d.</p> 	<p><b>TECHNICAL DATA SHEET</b></p> 	<p><b>IZ-KABELSKA</b></p> <p>Page 1/1</p> 
---	---	---

**Ident TTO:** RK16-27

**TOP TAPES TTO C S 2305**

**Property: Method: Specification: Unit:**

<b>Composition:</b>		Polyester nonwoven fabric, polyacrylate swelling powder, carbon black semi – conductive impregnation	
<b>Weight:</b>	ISO 9073/1	220+/-40	g/m <sup>2</sup>
<b>Thickness :</b>	ISO 9073/2	0,50+/-0,10	mm
<b>Tensile strenght MD:</b>	ISO 9073/3	>=50	N/cm
<b>Elongation MD:</b>	ISO 9073/3	>=10	%
<b>Surface resistance:</b>	DIN 54345	<1500	Ohmcm
<b>Volume resistance:</b>	DIN 54345	<10 <sup>6</sup>	Ohmcm
<b>Short term stability</b>	TTO method	230	°C
<b>Long term stability:</b>	IEC 216	90	°C
<b>Moisture content:</b>	TTO method	<10	%
<b>Swelling speed:</b>	TTO method	>=2	mm/1.min
<b>Swelling height:</b>	TTO method	>=3	mm/3.min

Edition	01	Tilen Bašin	Sandi Marini
Date	28.11.2016		
<b>Version</b>	<b>Date</b>	<b>Made by</b>	<b>Confirmed by</b>